

# [ Compart Sidewalls

The ultra-flexible and tough Compart-Sidewalls are today the industrial standard in the belting world. They set up a benchmark in light handling applications. Available in various heights and colours, Compart-Sidewalls are particularly easy to fit.



#### **Compart description:**

- 100% urethane material, non porous
- · Very high cut resistance
- · Very strong mechanical resistance, ideal for heavy duty conveying
- 100% suitable for immediate food contact EC and FDA\*
- 100% suitable for welding on PU as well as on PVC belts

### Easy handling and fitting:

- Easy joining finish on site
- · Clean and precise fitting by hot air or cold-bonding
- · Packaged in 100 m rolls on wooden coils

#### **Applications:**

Compart-Sidewall fitted belts are used on the following conveying solutions :

- Inclined conveying: straight or swan neck up to 80° with cleats
- Horizontal conveying: conveying of bulk items and items of various sizes.
- On request: for example, belts equipped with several rows of sidewalls for the recycling industry.





<sup>\*</sup> Migration test passed with success according to the EC/1935/2004 regulation and the 2002/72/EC directive.





| Туре        | Colour |      |       | Height | Min. pulley Ø | Base width (mm) | Wave width (mm) | Dimensions (m |    | nm) | _  | Hardness |       |
|-------------|--------|------|-------|--------|---------------|-----------------|-----------------|---------------|----|-----|----|----------|-------|
|             | White  | Blue | Green | (mm)   | (mm)          | а               | b               | С             | d  | е   | f  | (kg/m)   | (ShA) |
| Compart 20  | 0      | •    | 0     | 20     | 40            | 30              | 20              | 5             | 25 | 2,5 | 23 | 0,17     | 85    |
| Compart 30  | 0      | •    | 0     | 30     | 60            | 30              | 20              | 5             | 25 | 2,5 | 23 | 0,22     | 85    |
| Compart 40  | 0      | •    | 0     | 40     | 80            | 30              | 20              | 5             | 25 | 2,5 | 23 | 0,27     | 85    |
| Compart 50  | 0      | •    | •     | 50     | 90            | 60              | 34              | 13            | 47 | 2,5 | 40 | 0,33     | 85    |
| Compart 60  | 0      | •    | •     | 60     | 110           | 60              | 34              | 13            | 47 | 2,5 | 40 | 0,37     | 85    |
| Compart 80  | 0      | •    | •     | 80     | 140           | 60              | 34              | 13            | 47 | 2,5 | 40 | 0,53     | 85    |
| Compart 100 | 0      |      | 0     | 100    | 180           | 70              | 34              | 18            | 52 | 3   | 40 | 0,63     | 85    |






## The Compart-Sidewalls provide:

- An outstanding mechanical resistance
- · A quick and neat joining finish
- A very long service life
- An EC and FDA food certification

#### FITTING EXAMPLES WITH CLEATS



Standard fitting



Fitting of cleats tangent to the Compart's wave



Fitting of cleats that connect to the back of the waves



Our Compart-Sidewalls are also available in other materials such as: Polyolefin (for the tobacco industry), or Polyester. We also manufacture PU Compart in specific colours (for example: apple green).