

TECHNICAL DATA SHEET



ISO 9001



Validation date: 19/05/2009

STANDARD RANGE 1PURB25H/CW

CONVEYOR BELT TPU WHITE

Complies with FDA and EU regulations for conveying of foodstuff

CONSTRUCTION

- 1** 1-ply polyester fabric
- PUR** TPU polyurethan
- B** Colour : white
- 25** Top cover thickness : 0,25 mm
- H** Hard mat top cover
- C** 80N/mm fabric, rigid in weft, antistatic
- W** Impregnated backside

MAIN TECHNICAL DATA


- Top cover:** hardness: 92 Sh.A surface: mat, smooth
- Total thickness:** 0,70 mm \pm 0,1 mm per ply
- Weight per m²:** 760 g \pm 10%
- Friction Coefficient on steel slider bed:** 0,20 \pm 20%
- Manufacturing width:** 2 000 mm
- Temperatures:**
 - * Product temperature: -40°C to +90°C
 - * Ambient temperature: -25°C to +60°C
- Type of support:** Slider bed

MECHANICAL DATA

Tolerances: +20% -10%

- Breaking load:** 60 N/mm
- Load for 1% extension:** 5 N/mm
- Maximum working tension:** 8 N/mm

Pulley diameters:



These values are not linked to the requested \varnothing to pull the belt to rotation.

- Ambient temperature: from 0°C to +8°C: add +50%
- from 0°C to -25°C: add +100%

ENDLESS JOINTINGS

- Top heating plate: 170°C \pm 10°C
- Bottom heating plate: 130°C \pm 10°C
- Time: 1 mn \pm 1 mn
- Pressure: 1,0 bar \pm 0,5 bar
- Additional material (powder or film): none

These recommendations may vary according to the equipment used and press heating system.

Splicing methods to be used:

DS (finger joint)



Fasteners: None

Accessories that may be fitted on this belt: None

These data are subject to modification. Please make sure of their validity.
REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France

Tél.: +33 (0)4 78 91 81 01

Fax: +33 (0)4 78 91 05 09

www.reveyron.com

E.mail: info@reveyron.fr