

TECHNICAL DATA SHEET



ISO 9001



Validation date: 21/09/2010

STANDARD RANGE 2PURX30/FHR

CONVEYOR BELT TPU BLUE

Complies with FDA and EU regulations for conveying of foodstuff

CONSTRUCTION

2	2-ply polyester fabric
PUR	TPU polyurethan
X	Colour : blue RAL 5015
30	Top cover thickness : 0,35 mm
F	120N/mm fabric, flexible in weft
HR	"Rice grain" positive pattern, easy to clean

MAIN TECHNICAL DATA


Top cover:	hardness: 92 Sh.A surface: mat, smooth
Total thickness:	2,30 mm \pm 0,1 mm per ply
Weight per m²:	2 600 g \pm 10%
Friction Coefficient on steel slider bed:	0,50 \pm 20%
Manufacturing width:	2 000 mm
Temperatures:	
* Product temperature:	-40°C to +90°C
* Ambient temperature:	-25°C to +60°C
Type of support:	Slider bed, rollers, PEHD...

MECHANICAL DATA

Tolerances: +20% -10%

Breaking load:	180 N/mm
Load for 1% extension:	14 N/mm
Maximum working tension:	20 N/mm

Pulley diameters:



These values are not linked to the requested \varnothing to pull the belt to rotation.

Ambient temperature: from 0°C to +8°C: add +50%
from 0°C to -25°C: add +100%

ENDLESS JOINTINGS

Top heating plate:	160°C \pm 10°C
Bottom heating plate:	160°C \pm 10°C
Time:	2 mn \pm 1 mn
Pressure:	2,0 bar \pm 0,5 bar
Additional material (powder or film):	none


These recommendations may vary according to the equipment used and press heating system.

Splicing methods to be used:

DS (finger joint)



PE
step overlap



DS/DEC
(double finger joint)



Fasteners:

SL01 - SL02 - Sécura 01 -
Sécurinox 1 - Minibelt - Sécuri
G2

Accessories that may be fitted on this belt:

Except for some cases, this belt
can be fitted out with : guiding
profiles, cleats, sidewalls

These data are subject to modification. Please make sure of their validity.
REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France

Tél.: +33 (0)4 78 91 81 01

Fax: +33 (0)4 78 91 05 09

www.reveyron.com

E.mail: info@reveyron.fr