



TPU and PVC Tracking Guides and Profiles



Profile type	Material	Colours					Dimensions			Min. Pulley Ø		Hardness (ShA)	Weight (g/m)	Quantity (ml)
		White	Blue	Blue-green	Dark Green	Translucent	(mm)			(mm)				
							A	B	C	Back side	Top side			
CR = notched														
TR6/4	TPU	○	●				6	4	4	35	40	70	30	250
TR8/5	TPU	○	●	●			8	5	5	50	60	70	34	250
TR10/6	TPU	○	●	●			10	6	6	60	80	70	60	250
TR13/8	TPU	○	●	●		○	13	8	8	90	110	70	93	125
TR17/11	TPU	○	●	●			17	11	10	120	140	70	174	125
TR22/14	TPU					○	22	14	13	150	170	62	265	75
TR6/4CR	TPU	○	●				6	4	4	25	35	70	23	250
TR8/5CR	TPU					○	8	5	5	40	40	60	34	250
TR10/6CR	TPU	○	●				10	6	6	50	90	70	60	250
TR13/8CR	TPU	○	●				13	8	8	80	100	70	93	125
TR17/11CR	TPU					○	17	11	10	100	120	70	174	125
R10/10	TPU	○	●				10	10	-	100	140	70	125	200
TR8/5	PVC	○	●		●		8	5	5	40	60	60	33	250
TR10/6	PVC	○	●		●		10	6	6	60	80	60	57	250
TR13/8	PVC	○	●		●		13	8	8	80	120	60	88	125
TR17/11	PVC	○	●		●		17	11	10	120	150	60	164	125
TR17/15	PVC	○			●		17	15	8	120	180	60	230	200
TR22/14	PVC	○			●		22	14	13	160	240	60	265	75
TR10/6CR	PVC	○	●		●		10	6	6	45	100	60	57	250
TR13/8CR	PVC	○	●		●		13	8	8	60	130	60	88	125
TR17/11CR	PVC	○			●		17	11	10	100	180	60	164	125
R10/10	PVC	○			●		10	10	-	90	120	55	125	200

Other TPU or PVC rectangular profiles are available on request



Thickness	Material	Colours			Width	Min. Pulley Ø	Hardness
		White	Blue	Blue-Green			
b (mm)					A max (mm)	(mm)	(ShA)
2	TPU	○	●		60	30	85
2,5	TPU	○	●	●	60	40	85
3	TPU	○	●	●	60	50	85
4	TPU	○		●	60	80	85
5	TPU			●	60	120	85
6	TPU	○			40	140	85
8	TPU	○			30	160	85
6	PVC	○			40	90	70

Important: the indicated pulley diameter is based on a usage at 20°C.

Instructions for V-groove on pulleys

