# TECHNICAL DATA SHEET



Validation date: 21/09/2017

STANDARD RANGE 1PURB55HR/LW-2500

#### **CONVEYOR BELT TPU WHITE**

Complies with FDA and EU regulations for conveying of foodstuff

#### CONSTRUCTION

1 1-ply polyester fabric **PUR** TPU polyurethan

B Colour : white

55 Top cover thickness: 0,60 mm

**HR** "Rice grain" positive pattern, easy to clean

L 115N/mm fabric, rigid in weftW Impregnated backside

## MAIN TECHNICAL DATA

Top cover: hardness: 85 Sh.A surface: "Rice grain"pattern

Total thickness: 1,15 mm  $\pm$  0,1 mm per ply

Weight per m<sup>2</sup>: 1 150 g  $\pm$  10% Friction Coefficient on steel slider bed: 0,20  $\pm$  20%

Manufacturing width: 2 500 mm

Temperatures:

\* Product temperature: -40°C to +90°C \* Ambient temperature: -25°C to +60°C

Type of support: Slider bed

MECHANICAL DATA

Tolerances: +20% -10%

Breaking load:90,0N/mmLoad for 1% extension:6,0N/mmMaximum working tension:10,0N/mm

**Pulley diameters:** (recommended as a minimum with a 20°C ambient temperature)

N te

Minimum drive and tension: Ø 8 mm

Minimum reverse flexing: Ø 20 mm

These values are not linked to the requested  $\varnothing$  to pull the belt to rotation.

Ambient temperature: from 0°C to +8°C: add +50%

from 0°C to -25°C: add +100%

## **ENDLESS JOINTINGS**


Top heating plate:  $160^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Bottom heating plate:  $145^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Time:  $1 \text{ mn} \pm 1 \text{ mn}$ Pressure:  $2,0 \text{ bar } \pm 0,5 \text{ bar}$ 

Additional material (powder or film): none

These recommendations may vary according to the equipment used and press heating system.

## Splicing methods to be used:

DS (finger joint)



Fasteners: None

Accessories that may None be fitted on this belt:

These data are subject to modification. Please make sure of their validity. REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France

Tél.: +33 (0)4 78 91 81 01 Fax: +33 (0)4 78 91 05 09 www.reveyron.com

w.reveyron.com E.mail: info@reveyron.fr