TECHNICAL DATA SHEET



Validation date: 17/01/2017

CUSTOMIZED MANUFACTURING 1PURX25MAT/FW

CONVEYOR BELT TPU BLUE

Complies with FDA and EU regulations for conveying of foodstuff

CONSTRUCTION

1-ply polyester fabric PUR TPU polyurethan

Colour: blue RAL 5015 X Top cover thickness: 0,25 mm 25

Mat finish MAT

125N/mm fabric, flexible in weft F

W Impregnated backside

MAIN TECHNICAL DATA

Top cover: hardness: 85 Sh.A surface: mat, smooth

Total thickness: $0.90 \text{ mm } \pm 0.1 \text{ mm per ply}$

± 10% Weight per m2: 950 g ± 20% Friction Coefficient on steel slider bed: 0,20

Manufacturing width: 2 000 mm

Temperatures:

-40°C to +90°C * Product temperature: -25°C to +60°C * Ambient temperature:

Slider bed Type of support:

Tolerances: +20% -10% MECHANICAL DATA

Breaking load: 110 N/mm 5 N/mm Load for 1% extension: 10 N/mm Maximum working tension:

(recommended as a minimum with a 20°C **Pulley diameters:** ambient temperature)

Minimum drive and tension:

Ø8 mm

Minimum reverse flexing: Ø 20 mm

These values are not linked to the requested Ø to pull the belt to

rotation.

from 0°C to +8°C; add +50% Ambient temperature:

Tél.: +33 (0)4 78 91 81 01

from 0°C to -25°C: add +100%

ENDLESS JOINTINGS

Top heating plate: 150°C ± 10°C Bottom heating plate: 140°C ± 10°C Time: 1 mn ± 1 mn Pressure: 1,5 bar \pm 0,5 bar

Additional material (powder or film): none

These recommendations may vary according to the equipment used and press heating system.

Splicing methods to be used:

DS (finger joint)



Fasteners: None

Accessories that may

be fitted on this belt: None

These data are subject to modification. Please make sure of their validity. REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France

Fax: +33 (0)4 78 91 05 09 www.reveyron.com

E.mail: info@reveyron.fr