# TECHNICAL DATA SHEET



Validation date: 24/04/2019

ISO 9001

STANDARD RANGE 2PURX30X/LX30

## **CONVEYOR BELT TPU BLUE**

Complies with FDA and EU regulations for conveying of foodstuff

#### CONSTRUCTION

2 2-ply polyester fabricPUR TPU polyurethan

X Colour : blue RAL 501530 Top cover thickness : 0,30 mm

X Blue PU inner ply

LX30 125 N/mm fabric, rigid in weft, smooth PU bottom cover (0,30 mr

### **MAIN TECHNICAL DATA**

Top cover: hardness: 92 Sh.A surface: Mat

Total thickness: 2,90 mm  $\pm$  0,1 mm per ply

Weight per m<sup>2</sup>:  $3 560 \text{ g} \pm 10\%$ Friction Coefficient on steel slider bed:  $0,50 \pm 20\%$ 

Manufacturing width: 2 000 mm

Temperatures:

\* Product temperature: -40°C to +90°C \* Ambient temperature: -25°C to +60°C

Type of support: Rollers

MECHANICAL DATA

Tolerances: +20% -10%

Breaking load:180,0N/mmLoad for 1% extension:13,0N/mmMaximum working tension:20,0N/mm

Pulley diameters: (recommended as a minimum with a 20°C

ambient temperature)

Minimum drive and tension: Ø 80 mm

Minimum reverse flexing: Ø 80 mm

These values are not linked to the requested Ø to pull the belt to rotation

Ambient temperature: from 0°C to +8°C: add +50%

Tél.: +33 (0)4 78 91 81 01

from 0°C to -25°C: add +100%

## **ENDLESS JOINTINGS**

Top heating plate:  $150^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Bottom heating plate:  $150^{\circ}\text{C} \pm 10^{\circ}\text{C}$ Time:  $1 \text{ mn} \pm 1 \text{ mn}$ Pressure:  $2,0 \text{ bar } \pm 0,5 \text{ bar}$ 

Additional material (powder or film):

These recommendations may vary according to the equipment used and press heating system.

### Splicing methods to be used:


DS (finger joint)



PE step overlap



DS/DEC (double finger joint)



Fasteners: Minibelt - SL02 - Sécuri-P3

Accessories that may be fitted on this belt:

Except for some cases, this belt can be fitted out with: guiding profiles,

cleats, sidewalls

These data are subject to modification. Please make sure of their validity.

REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.



247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France Fax: +33 (0)4 78 91 05 09 www.reveyron.com

E.mail: info@reveyron.fr

