












TPU-Stollen



	Type	Material	Farben					Abmessungen		Min. Umlenk-Ø	Härte	Optionen			Gewicht	Profillängen und Losgrößen				
			Weiß	Blau	Grünblau	Schwarz	Transparent	(mm)				(ShA)	U-Form	V-Form		Comparts		(g/m)	Länge (ml)	Losgröße (ml)
								B	H							im Wellental	an der Welle			
	T20	TPU	○	●	●			8	20	50	92			√	√	90	3	33/99		
	T30	TPU	○	●	●			9	30	50	92			√	√	150	3	33/99		
	T40	TPU	○	●	●			9	40	50	92			√	√	200	3	33/99		
	T50	TPU	○	●	●			9	50	50	92			√	√	300	3	33/99		
	T60	TPU	○	●	●			11	60	50	92			√	√	350	3	33/99		
	TI30	TPU	○	●	●			9	30	50	85				√	175	3	33/96		
	TI40	TPU	○	●	●			9	40	50	85				√	220	3	33/63		
	TI60	TPU	○	●	●			11	60	50	92				√	400	3	33/99		
	SP20-6	TPU	○	●	●			6	20	80	85				√	145	3	33		
	SP30-6	TPU	○	●	●			6	30	80	85				√	215	3	33		
	SP40-6	TPU	○	●	●			6	40	80	85				√	290	3	33		
	SP50-6	TPU	○	●	●			6	50	80	85				√	360	3	33/99		
	SP60-6	TPU	○	●	●			6	60	80	85				√	430	3	33/99		
	SP80-6	TPU	○	●	●			6	80	80	85				√	570	3	27/54		
	SP100-6	TPU	○	●				6	100	80	85				√	740	3	27/54		
	SP150-6	TPU	○	●				6	150	80	85					1200				
	SP20-10	TPU	○	●				10	20	120	85				√	240	3	27		
	SP30-10	TPU	○	●				10	30	120	85				√	360	3	27		
	SP40-10	TPU	○	●				10	40	120	85				√	480	3	27		
	SP50-10	TPU	○	●				10	50	120	85				√	600	3	27		
	SP60-10	TPU	○	●				10	60	120	85				√	720	3	27		
	SP80-10	TPU	○	●				10	80	120	85				√	960	3	27/54		
	SP100-10	TPU	○	●				10	100	120	85				√	1210	3	27/54		
	SP150-10	TPU	○	●				10	150	120	85					1820				
	RH30	TPU	○		●			32	30	100	76	√			√	380	3	33/99		
	RH40	TPU	○		●			32	40	100	76	√			√	450	3	33/99		
	RH50	TPU	○	●	●			32	50	110	76	√			√	700	3	33/99		
	RH60	TPU	○		●			32	60	120	76	√			√	950	3	33/99		
	RH80	TPU	○	●				31	80	140	76	√			√	1000	3	33/66		
	TM30*	TPU	○	●		●		55	30	120	92					320	2	30/60		
	TM40*	TPU	○	●				55	40	120	92					415	2	30/60		
	TM50*	TPU	○	●		●		55	50	120	92					500	2	30/60		
	TM60*	TPU	○	●				55	60	120	92					600	2	30/60		
	R10/10	TPU	○	●				10	10	60	70		√			125	1	200		
	R40/6	TPU	○					40	6	110	85					290				
	R30/8	TPU	○					30	8	150	85					290				
	TR6/4	TPU	○	●				6	4	40	70		√			30	1	250		
	TR8/5	TPU	○	●	●			8	5	50	70		√			34	1	250		
	TR10/6	TPU	○	●	●			10	6	50	70		√			60	1	250		
	TR13/8	TPU	○	●	●		○	13	8	80	70		√			93	1	250		
	TR17/11	TPU	○	●	●			17	11	120	70		√			174	1	125		
	TR22/14	TPU					○	22	14	150	62		√			265	1	75		
	D60-80	TPU	○					14	60	80	70		√			10 g				
	D105-80	TPU	○					21	105	90	70		√			15 g				
	D105-85	TPU		●				21	105	90	85		√			16 g				

PVC-Stollen




Type	Material	Farben				Abmessungen		Min. Umlenk-Ø	Härte	Optionen			Gewicht	Profilängen und Losgrößen		
		Weiß	Blau	Grünblau	Apfelgrün	(mm)				(ShA)	U-Form	V-Form		Comparts		(g/m)
						B	H	im Wellental	an der Welle							
T20	PVC	○	●	●		20	20	60	60				√	180	3	33/306
T30	PVC	○	●	●		24	30	80	60				√	350	3	33/225
T40	PVC	○	●	●		24	40	80	60				√	430	3	33/156
T50	PVC	○	●	●		28	50	100	60				√	630	3	33/156
T60	PVC	○	●	●		28	60	100	60				√	790	3	33/81
T75	PVC	○	●		●	32	75	120	60				√	1080	2	32/96
T100	PVC	○	●	●		32	100	120	67				√	1500	3	33/66
RH30	PVC	○		●		32	30	90	67	√			√	380	3	33/99
RH40	PVC	○		●		32	40	90	67	√			√	450	3	33/99
RH50	PVC	○	●	●		32	50	100	67	√			√	700	3	33/99
RH60	PVC	○	●	●		30	60	110	67	√			√	950	3	33/99
RH80	PVC	○	●	●		31	80	120	67	√			√	1000	3	33/66
RH100	PVC	○		●		29	100	140	67				√	1400	3	33/66
TM50*	PVC		●		●	55	50	80	●65 ●80					650	2	30/60
TM60*	PVC		●		●	55	60	80	●65 ●80					780	2	30/60
TM75*	PVC		●		●	55	75	80	●65 ●80					975	2	30/60
TMI50*	PVC		●		●	55	50	80	●65 ●80				√	650	1,2	30/60
TMI60*	PVC		●		●	55	60	80	●65 ●80				√	820	1,2	30/60
TMI75*	PVC		●		●	55	75	80	●65 ●80				√	975	1,2	30/60
R10/10	PVC	○	●	●		10	10	60	60		√			125	1	200
R40/6	PVC	○				40	6	90	60					290		50
TR8/5	PVC	○	●	●		8	5	40	○55 ●60		√			33	1	250
TR10/6	PVC	○	●	●		10	6	50	○55 ●60		√			57	1	250
TR13/8	PVC	○	●	●		13	8	70	○55 ●60		√			88	1	125
TR17/11	PVC	○	●	●		17	11	100	○55 ●60		√			164	1	125
TR17/15	PVC	○		●		17	15	100	○55 ●60		√			230	1	200
TR22/14	PVC	○		●		22	14	140	○55 ●60		√			265	1	75
TR45/17	PVC	○				45	17	200	76					690	1	100

* Gewebeerstärkte Stollen

Andere Stollenhöhen auf Anfrage verfügbar

TPU-Flachbänder

als Rollen oder Zuschnitte



Type	Farben	Produktionsbreite	Gesamtsärke	Härte	Ausführung	Lebensmittelzulassung
PUX1M	●	650	1,00	85	Matt	√
PUB2M / PUX2M / PUV2M / PUN2M	○ ● ● ●	650	2,00	85	Matt	√
PUB3M / PUX3M / PUV3M	○ ● ●	650	3,00	85	Matt	√
PUB4M / PUV4M	○ ●	650	4,00	85	Matt	√
PUV5M	●	650	5,00	85	Matt	√