TECHNICAL DATA SHEET



Validation date: 07/05/2013

STANDARD RANGE 2PURX90/LHR

CONVEYOR BELT TPU BLUE

Complies with FDA and EU regulations for conveying of foodstuff

CONSTRUCTION

2 2-ply polyester fabricPUR TPU polyurethan

X Colour : blue RAL 5015

90 Top cover thickness: 0,90 mmL 115N/mm fabric, rigid in weft

HR "Rice grain" positive pattern, easy to clean

MAIN TECHNICAL DATA

Top cover: hardness: 92 Sh.A surface: Mat

Total thickness: 0,134" $\pm 0,0039$ " per ply

Weight per Sq Ft: 0,82 lbs \pm 10% Friction Coefficient on steel slider bed: 0,50 \pm 20%

Manufacturing width: 78,74"

Temperatures:

* Product temperature: -40°F to +194°F * Ambient temperature: -13°F to +140°F

Type of support: Slider bed, rollers, PEHD..

MECHANICAL DATA

Tolerances: +20% -10%

Breaking load:1 028lbs/in.Load for 1% extension:74lbs/in.Maximum working tension:114lbs/in.

Pulley diameters: (recommended as a minimum with a 70°F ambient temperature)

Minimum reve

Minimum drive and tension: Ø 3,94"

Minimum reverse flexing: Ø 6,30"

These values are not linked to the requested Ø to pull the belt to rotation.

Ambient temperature: from 32°F to +46°F: add +50%

from 32°F to -13°F: add +100%

ENDLESS JOINTINGS

Top heating plate: $302^{\circ}F \pm 20^{\circ}F$ Bottom heating plate: $302^{\circ}F \pm 20^{\circ}F$ Time: $2 \text{ mn} \pm 1 \text{ mn}$ Pressure: $29 \text{ psi} \pm 7 \text{ psi}$

Additional material (powder or film): none

These recommendations may vary according to the equipment used and press heating system.

Splicing methods to be used:

DS (finger joint)



PE step overlap



DS/DEC (double finger joint)

Fasteners: SL02 - Sécura 02 - Sécurinox 2 -

Minibelt

Accessories that may be fitted on this belt:

Except for some cases, this belt can be fitted out with: guiding profiles, cleats,

sidewalls

These data are subject to modification. Please make sure of their validity.
REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France

Tel.: +33 4 78 91 81 01 Fax: +33 4 78 91 05 09 www.reveyron.com E.mail: info@reveyron.com