

TECHNICAL DATA SHEET



ISO 9001



Validation date: 04/05/2015

STANDARD RANGE 2SI30/CW

CONVEYOR BELT SILICONE CLEAR

Complies with FDA regulations for conveying of foodstuff

CONSTRUCTION

- 2** 2-ply polyester fabric
- SI** Silicone / PVC
- 30** Top cover thickness : 0,25 mm
- C** 80N/mm fabric, rigid in weft, antistatic
- W** Impregnated backside

MAIN TECHNICAL DATA


Top cover: hardness: 40 Sh.A surface: glossy, smooth	
Total thickness:	0,065" \pm 0,0039 " per ply
Weight per Sq Ft:	0,37 lbs \pm 10%
Friction Coefficient on steel slider bed:	0,20 \pm 20%
Manufacturing width:	118,11"
Temperatures:	
* Product temperature:	14°F to +176°F
* Ambient temperature:	14°F to +176°F
Type of support:	Slider bed

MECHANICAL DATA

Tolerances: +20% -10%

Breaking load:	799 lbs/in.
Load for 1% extension:	51 lbs/in.
Maximum working tension:	69 lbs/in.

Pulley diameters: (recommended as a minimum with a 70°F ambient temperature)



These values are not linked to the requested \varnothing to pull the belt to rotation.

Ambient temperature: from 32°F to +46°F: add +50%
from 32°F to 23°F: add +100%


ENDLESS JOINTINGS

Top heating plate:	329°F \pm 20°F
Bottom heating plate:	329°F \pm 20°F
Time:	2 mn \pm 1 mn
Pressure:	29 psi \pm 7 psi
Additional material (powder or film):	none

These recommendations may vary according to the equipment used and press heating system.

Splicing methods to be used:

PE
step overlap



DS/DEC
(double finger joint)



Fasteners: SL00 - AGRAFE PLAST - AZ5 - SECURI-P2

Accessories that may be fitted on this belt: Except for some cases, this belt can be fitted out with longitudinal tracking profiles

These data are subject to modification. Please make sure of their validity.
REVEYRON S.A. should not be held responsible when the data sheet used is not valid anymore.

reveyron S.A.

247, route du Mas Rillier, Les Echets - 01700 MIRIBEL - France

Tel.: +33 4 78 91 81 01

Fax: +33 4 78 91 05 09

www.reveyron.com

E.mail: info@reveyron.com